

SPECKLED S & PUZZLETILE

Speckled S is designed for easy and fast installation and a virtually seamless appearance. Speckled S is a great solution for anyone that needs a surface with outstanding durability in a cost-effective system. Custom logos are also available.

PuzzleTile is portable, affordable, easy to install, and requires no adhesive!



PRODUCT FEATURES

- Sound and shock absorbent
- Easy installation and maintenance
- Slip resistant, wet or dry
- Extremely durable
- Low life cycle costs
- Made in the U.S.A.

PRODUCT OPTIONS

Roll goods and interlocking tiles are available standard in an 8 millimeter thickness. Custom thicknesses and tile options are also available.

Speckled S:

8mm x 48" (1.2m) x 25LF

8mm x 48" (1.2m) x 50LF

PuzzleTile:

8mm x 23" (58cm) x 23" (58cm)*

CS00, CS01, CS02 are available in center, border, and corner tiles.

All other options come in center tiles only and minimum quantities apply.

*For all custom options, please contact your local representative to determine availability, pricing, minimums, and lead times.

PHYSICAL DATA

PERFORMANCE CRITERIA DENSITY

Tensile Strength
Flexibility
Static Load (1000 lb/in²)
Coefficient of Friction
Thermal Conductivity
Ambient Noise Reduction
Impact Insulation Class
Sound Transmission Coefficient
Ball Rebound

TEST METHOD

ASTM D412
ASTM F137
ASTM F970
ASTM 2047
ASTM C518
ASTM C423
ASTM E492
ASTM 413
EN 12235

RESULTS

200 lb/in² min.
Pass 1/4-inch mandrel
Less than 0.020-inches
Greater than 0.9-inches
0.406 BTU-in/hr-ft²-°F
0.10 Sabin/ft²
45 Minimum
45 Minimum
Pass