

Product Options



14.5mm (2.5mm+12mm) x 48" (1.2m)



14.5mm (2.5mm+12mm) x 23" (58cm) x 23" (58cm)

Physical Data

PERFORMANCE CRITERIA	TEST	RESULT
Tensile Strength	ASTM D 412	>200 PSI
Flexibility 1/4" mandrel	ASTM F 137	Pass
Thermal Conductivity	ASTM C 518	>0.4
Static Load Limit	ASTM F 970 @ 250PSI	0.009" Typical
Coefficient of Friction	ASTM D 2047	> 0.9
V.O.C. Compliant	ASTM D 5116	Yes
Abrasion Resistance	ASTM D 3389 / EN 649	<1g, 100 cycles
Pill Test	ASTM D 2859	Pass
Vertical Deflection / Deformation	ASTM F 2772	2.66mm
Surface Effect Slip Resistance	ASTM F 2772	Pass
Ball Rebound	ASTM F 2772	98.8%
Force Reduction	ASTM F 2772	35.7%

Can a track lessen the amount of forceful impact on your body, and keep you running longer with less joint pain?



Yes.

Stacked Performance Rally

is a 14.5mm surface tailored for heavy conditioning and is available in both rolls and interlocking tiles.



What does it take to be a floor?

- Durable
- Sustainable
- Affordable
- Ease of Maintenance
- Slip Resistant

With a durable wear layer made from vulcanized EPDM rubber, this product resists the scuffing and marking that is common in strength and conditioning applications.




Can a floor do more? Yes.

This 14.5mm product showcases a dynamic force reduction of 35.40%. This dual durometer system is engineered to absorb the impact force related to aggressive functional training, providing an ergonomically advanced surface that works in concert with the body.


Applications



Cardio



Light Weights



Moderate Weights



Extreme Functional Training



Tracks



Strength Equipment



Functional Training

