



PLAYGUARD

SAFETY SURFACING

Technical Specifications

Critical Fall Height and Physical Dimensions					
Thickness	Weight (lbs.) Each (Not less than)		Critical Fall Height (ft.)		
	Softpave Pigmented & Non-Pigmented	Carnival/Turf Tile	Softpave Pigmented & Non-Pigmented	Carnival	Turf Tile
2-1/2"	25	27	6	6	5
2-1/2" & 2-1/8" Polyfoam	29	31	10	10	11

Packaging Information				
Full Pallet Weight (lbs.)				
Thickness	Pieces/Pallet	Softpave Pigmented & Non-Pigmented	Carnival/Turf Tile	Pallet Height
2-1/2"	100	2,560	2,760	66"
2-1/8" x 4' x 6' (Polyfoam Sheet)	23	680	680	52"

Physical Testing - Typical Results			
Characteristic	Test Method	Softpave Pigmented & Non-Pigmented Tile	Carnival
Density*	ASTM D297	58 lb./ft ³	80 lb./ft ³
Tensile Strength*	ASTM D412, DIE C	180 lb./in ²	250 lb./in ²
Elongation at Break*	ASTM D412, DIE C	50%	70%
Abrasion Test*	ASTM D3389	Less than 0.200g lost	Less than 0.200g lost
Coefficient of Friction*	ASTM D2047	0.8	0.8
Flammability	ASTM D2859 (Burning Pill Test)	8 of 8 samples passed	8 of 8 samples passed
Wheel Chair Accessibility	ASTM F1951-08	Pass	Pass
Lead Content	US EPA Method 3052:1996	Pass	Pass

*testing on wear layer surface only

FIFTEEN YEAR* LIMITED WARRANTY INFORMATION - Materials, Workmanship, and Performance	
Number of years from date of original installation to date of claim	Percentage of product purchase price found to be defective or non-compliant
0-6	100%
More than 6, but less than 7	60%
More than 7, but less than 8	40%
More than 8, but less than 9	30%
More than 9, but less than 10	20%
More than 10, but less than 12	10%
More than 12, but less than 15	5%



To verify product certification, visit www.ipema.org



*Softpave Pigmented & Non-Pigmented tiles are 10 year warranty only.

*Turf Tiles are 5 year warranty only.

* Any application other than children's playgrounds, or rooftop & patio adult pedestrian traffic use will need to be approved by the Ecore Playguard Division.